

Advisor II

ONE WAY ALPHANUMERIC PAGER



Features:

Message Slots	52 message
Cap Codes	4 individual cap Codes to allow the user to receive individual
Character Capacity	Up to 30,000 maximum character capacity
Display	Optimax® EL Electra Light for easy read ability 4 lines of text with up to 8 characters per line zoom feature
Message Preview	Allows the user to view the first line or each message for easy reference
Built-in Alarm Clock	
Event Alarm	Allows the user to set a one-time or daily alarm for up to 5 personal messages
User-Selectable Alerts	Includes Vibrating, Standard, Chirping Alerts, 7 different pleasing Alerts or No alerts (silent)
Selective Erase/ Erase	Allows the user to ease messages individually or all at once
Graphic Battery Gauge	Shows battery level



For more information, please contact:

3239 West 2nd Street
P.O. Box 2151
Grand Island, NE 68802

Phone:(308) 381-4000
Toll Free: (800) 658-0567
Fax: (308) 381-2801

Specification:

Audio Output	78 dB @ 12"
Battery	1.5v "AA" Alkaline
Channel Spacing	Wide Band
Frequency	VHF (POCSAG: 143-174 MHz Flex: 163-174 MHz) UHF (450-470) MHz 900MHz (929-932
Operating Temperature	+5C to +40C
Paging Protocol	POCSAG or FLEX
Selectivity	55dB
Sensitivity	4.0 to 8.0 uV/M
Spurious Image Rejection	50 dB
Type	Alphanumeric