

3239 West 2nd Street
P.O. Box 2151
Grand Island, NE 68802

Toll Free: (800) 658-0567
Phone: (308) 381-4000
Fax: (308) 381-2801

**MIDLAND
TELECOM**

**TELEPHONE SYSTEMS
OF NEBRASKA, INC**

www.midlandtelecom.com

MSK-R70

Mobile Camera



+



+



Features: Mobile Rear View Camera

- Compact, discreet appearance and miniature camera
- With IR, CCD color image automatically changed into B/W image in the dark
- Weatherproof housing for outdoor use
- Capable for day and night monitoring

Features: 7" Mobile Monitor

- Friendly OSD function Controls
- Automatic mirror Display in Rear gear
- Wide Range Power input 12-30VDC
- 2 CH Video / Audio Input

Features: 20M Min Din Cable

- 20M Min Din Cable



Specifications: 7" TFT LCD Mobile Monitor

LCD Panel	7 TFT Panel. R.G.B Stripe
LCD Display	1440(H)x234(V)
LCD Total Pixels	336960
LCD TV System	NTSC/PAL .Auto Selection
Brightness	400 cd/mm2
View Angle	L/R: 65° U/D: 45° / 65°
Video input signal	2 CH 1.0Vp-p Composite
Audio input signal	2 CH 3.0Vp-p~100m Vp-p
A/V Input Terminals	Mini Din Cable
Power/Cable	DC12V~30VDC/750mA
Power Supply	12 VDC /750mA ±10%/20M Single Cable (Mini-Din)
Operating Temp.	Work: 0°C ~ 60°C, Storage: -25°C ~ 80°C
Dimension (mm)	180(W) x 120(H) x 21(D) (W/O Bracket)
Weight (N.W)	0.44kg (W/O Bracket)

Specifications: Mobile Rear View Camera

Image Device	1/3" CCD image sensor
Picture Elements	NTSC: 510x492, PAL: 500x582
H. Sync Frequency	NTSC: 15.734KHz, PAL: 15.625KHz
V. Sync. Frequency	NTSC: 59.94Hz, PAL: 50Hz
SYNC System	Internal
Horizontal Resolution	420 TVL
Sensitivity	0 Lux Built-in IR LED (6 Unit of 850nm IR LED)
BLC	AUTO
Electronic Shutter	1/50(1/60) ~ 1/100,000 sec.
Gain Control	AUTO
Lens	2.8mm F2.0 Lens
Weight (N.W)	0.28kg
S/N Ratio	More than 48 dB (AGC off)
Video Output	1.0Vp-p, 75Ohm
Protection Class	IP 66
Power Supply	DC12V / 150mA
Power Consumption	170mA
Operating Temp.	Work: -10°C ~ +50°C, Storage: -30°C ~ +60°C
Dimensions (mm)	66(L) x 44(H) x 54.85(D)